



NOTES:

TECHNICAL CHARACTERISTICS:

1. VIBRATION: 100M/S2 (10~500HZ)
2. IMPEDANCE: 75 Ω
3. FREQUENCY RANGE: DC~1GHZ
4. WORKING VOLTAGE: 170V MAX
5. WITHSTAND VOLTAGE: 500V RMS

CONTACT RESISTANCE:

1. CENTER CONTACT: $\leq 10 \text{ M}\Omega$
2. OUTER CONTACT: $\leq 5 \text{ M}\Omega$
3. INSULATION RESISTANCE: $\geq 1000 \text{ M}\Omega$
4. VSWR : STRAIGHT: ≤ 1.20 , RIGHT ANGLE: ≤ 1.30
5. DURABILITY (MATING): ≥ 500 TIMES MIN;

ENVIRONMENTAL:

1. STORAGE: $-40^\circ \text{ TO } +85^\circ$
2. OPERATION: $0^\circ \text{ TO } 70^\circ$

MATERIAL: ABS; COPPER (CU)

Keystone Module SAT/antenna

- 16.2 mm width, Coaxial female > F female
- for installation in the KeyStone patch panels, wall sockets, housing and so on
- plastic housing

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 04.03.2020	nw	Keystone Module SAT/antenna 	
		gepr.: 04.03.2020	nw		
		Norm:		Zeichnungs-Nr.: 79936	von
Änderungen vorbehalten / Subject to change					