



LPW-BC3G-26

- Low profile, vandal & tamper-proof design
- Simple adhesive pad or screw fix installation
- Covers global cellular & LTE bands
- Suitable for mounting on metallic or non-metallic surfaces*

The Panorama LPW range of antennas are designed to decrease the lifetime cost of M2M and smart metering installations by offering a robust, effective antenna that is easy to install and lasts the lifetime of the installation without the need for maintenance.


The antenna offers ground-plane independent Omni-directional performance across global cellular and LTE bands making it a versatile solution for any number of applications. The efficient element design ensures a high first-time connection rate and an ongoing, robust communications link even in problematic coverage areas.

The antenna can be installed using the supplied automotive-grade adhesive pad or via the integrated screw mounting bosses. If the antenna is panel mounted the cable can be routed through a hole in the adhesive pad to run invisibly into the panel behind.

*Performance may change based on the mounting surface.

Technical Drawing


LPW-BC3G-26 Shown




LPW-BC3G-26-2SP

Electrical Data	
Frequency Range (MHz)	698-960, 1710-2700
Operational Band	LTE 700 / LTE 800 / AMPS 850 / GSM 900 / GSM 1800 / PCS 1900 / AWS / 3G UMTS 2100 / LTE 2600
Typical VSWR	< 2:1
Typical Peak Gain: Isotropic	2dBi
Compared to ¼ wave	0dB
Pattern	Omni-directional
Impedance	50Ω
Max Input Power (W)	20W
Mechanical Data	
Height	19.6 (0.77")
Dimensions (mm)	Length 165 (6.5")
	Width 32 (1.26")
Operating Temp (°C)	-30° / +70°C (-22°F / 158 °F)
Material	ASA
Colour	Telegray RAL 7047
Ingress protection	Equivalent to IP66 when properly installed
Mounting Data	
Fixing	Industrial grade acrylic adhesive pad / 2x 4.8mm (0.18")screws
Cable Data	
Type	RG174
Thickness (mm)	2.8 (0.11")
Length (m)	2 (6' 6")
Termination	SMA Plug**

Typical VSWR of Antenna in Free Space*



Typical VSWR on 350 x 350mm Ground Plane*




**Other connectors and micro connectors available


3D Patterns - Cell

3D Patterns of Antenna in Free Space


Typical 3D Pattern (700MHz)




Typical 3D Pattern (800MHz)




Typical 3D Pattern (900MHz)




Typical 3D Pattern (1800MHz)




Typical 3D Pattern (1900MHz)




Typical 3D Pattern (2100MHz)



Typical 3D Pattern (2400MHz)




Typical 3D Pattern (2600MHz)




E and H Plane Patterns Mounted on 350 x 350mm Ground Plane


Typical H-Plane (750MHz)




Typical E-Plane (750MHz)




Typical H-Plane (850MHz)




Typical E-Plane (850MHz)




Typical H-Plane (900MHz)




Typical E-Plane (900MHz)




Typical H-Plane (1800MHz)




Typical E-Plane (1800MHz)




Typical H-Plane (1900MHz)




Typical E-Plane (1900MHz)




Typical H-Plane (2100MHz)



Typical E-Plane (2100MHz)



Typical H-Plane (2600MHz)



Typical E-Plane (2600MHz)

