


ANTENNAS | GPS-1 SERIES

GPS/GLONASS ACTIVE ANTENNA

1575.42 MHz / 1602 MHz, 20 dBi



- GPS / GLONASS
- Robust, vandal-resistant, and waterproof (IP 69K)
- Ideal for positioning and timing systems for transportation, marine, and IoT/M2M use
- Ultra-versatile mounting options for easy installation



APPLICATION AREAS

Product Overview

Poynting's new V3 version of the GPS-1 antenna provides a compact design suitable for the IoT/M2M and transportation markets, where rugged and precise positioning and timing are essential. This updated enclosure with an external seal for the active GPS antenna simplifies implementation with its various mounting options. The GPS/GLONASS system frequency band operates at 1575.42/1602 MHz and can function at temperatures as low as -40°C.

Features


- Small & Low-profile (Ø100mm x 36mm (h))
- Careful mechanical design provides ruggedness, corrosion, water and dust resistance (IP 69K)
- Fire Resistant
- UV Stable Enclosure
- Easy installation; multi-implementation options available:
 - Spigot Mount
 - Magnetic Mount
 - Adhesive Tape Mount
 - Bracket Mount

Application Areas

- Industrial automation, robotic machinery and other M2M systems
- Transport, tracking (Busses, Utility & Public Safety)
- Mining Vehicles & Machinery communications and positioning (M2M & IoT)
- Agricultural machinery
- Marine: small boats, yachts.
- Clocking and timing systems



Antenna Overview

	
Ports	1
Frequency Bands	1575.42 MHz/1602 MHz
Polarisation	RHCP
LNA Peak Gain	20±3 dBi
Coax Cable Type	RTK-031
Coax Cable Length	2m
Connector Type	SMA (M)

*The coax cable & connector are factory mounted to the antenna

Electrical Specifications – GPS/Glonass Antenna

Frequency Range:	1575.42 MHz / 1602 MHz
LNA Gain (Max):	20±3 dBi
VSWR:	≤2:1
Working Voltage:	2.7 – 5 V
Working Current:	≤20mA
Noise Figure:	≤2 dB
Nominal Impedance:	50 Ω
Polarisation:	RHCP
Power Handling:	33 dBm
Coax Cable Loss:	0.71 dB/m @ 1500 MHz

Product Box Contents

Antenna:	A-GPS-0001-V3-01
Mounting Bracket:	Ø20 Threaded Spigots (Up to 60mm clamping thickness), Adhesive Surface Mounting & Magnetic Mount

Ordering Information

Commercial Name:	GPS-1
Order Product Code:	A-GPS-0001-V3-01
EAN Number:	6009716250055
EU Homologation Number:	E1*10R06/01*9551*00

Mechanical Specifications


Product Dimensions	Ø99.3 mm x 36 mm
Packaged Dimensions:	150 mm x 150mm x 120mm
Weight:	0.22 kg
Packaged Weight:	0.52 kg
Radome Material:	PC+ABS (Halogen free)
Radome Colour:	Pantone Black
Mounting Type:	Ø20 Threaded Spigot, Pole, Wall, Surface and Magnetic mount

Environmental Specifications, Certification & Approvals

Wind Survival:	≤220 km/h
Temperature Range (Operating):	-40°C to +80°C
Environmental Conditions:	Outdoor/Indoor
Water Ingress Protection Ratio/Standard:	IP 69K
Salt Spray:	MIL-STD 810G/ASTM B117
Operating Relative Humidity:	Up to 98%
Storage Humidity:	5% to 95% - non-condensing
Storage Temperature:	-40°C to +80°C
Enclosure Flammability Rating:	UL 94-HB, ECE-R118.02 Certified cables
Impact Resistance:	IK 10
Product Safety & Environmental:	Complies with CE and RoHS standards



Technical Drawing



Mounting Options

Many Mounting Possibilities – included as standard


Poynting's GPS-1 provides easy installation with multiple mounting options. This includes as standard:

- Spigot Mount - two different lengths included (35mm & 75mm)
- Vertical Pole mount (inner & outer mounting for smaller and larger poles)
- Horizontal Pole Mount (e.g., marine rails)
- Magnetic Mount
- Surface Mount (Double Sided Tape)
- Wall Mount




Spigot Mount

Removable 35mm & 75mm threaded spigot (included)




Vertical Pole Mount

Pole/Wall Mounting bracket (included)




Magnetic Mount

Magnetic Base (included)
For temporary and low mobility installations.




Horizontal Pole Mount

Pole/Wall Mounting bracket (included)



Surface Mount

Adhesive Surface Mounting (included) or can also be directly secured with longer M4 bolts (not included) to the female threaded inserts located in the antenna base



Wall Mount

Pole/Wall Mounting bracket (included)

Additional Accessories

See accessories technical specifications on www.poynting.tech

CONTACT POYNTING

Poynting Antennas (Pty) Ltd - Head Office

Unit 4, N1 Industrial Park,
Landmarks Avenue,
Samrand, 0157, South Africa

Phone: +27 (0) 12 657 0050

E-mail: info@poynting.tech

International Email: sales-global@poynting.tech

Poynting Europe

Regus Business Center Neue Messe Riem
Kronstadter Straße 4
81677 München
Germany

Phone: +49 89 7453 9002

E-mail: sales-europe@poynting.tech

Poynting USA

1804 Owen Court, Suite 104,
Mansfield,
TX 76063
USA

Phone: +1 817 533-8130

E-mail: sales-us@poynting.tech