

## **EAD/EADI Air Duster**

Page 1

EAD and EADI are non-flammable products designed for the safe removal of dust and airborne contamination from very delicate or inaccessible areas of electrical and electronic equipment. EAD is the standard version whereas EADI is the invertible version, which is particularly useful for very intricate equipment or items which cannot be moved for cleaning or maintenance.

- Inert, pure compressed gas for dust removal
- Ideal for removing particulates from inaccessible areas on delicate equipment
- Standard (EAD) or invertible (EADI) versions available
- Non-flammable propellant

### **Typical Properties**

Colour	Colourless
Flash Point (°C)	None
Boiling Point (°C)	-26.2
GWP (vs. CO <sub>2</sub> , 100yr ITH)	< 1

<b><u>Description</u></b>	<b><u>Packaging</u></b>	<b><u>Order Code</u></b>	<b><u>Shelf Life</u></b>
<u>Standard Airduster</u>	200ml Aerosol 400ml Aerosol	EAD200D EAD400D	48 months 48 months
<u>Invertible Airduster</u>	200ml Aerosol	EADI200D	48 months

### **Directions for Use**

EAD should be used in a vertical position or at an angle of not greater than 60° to the vertical otherwise a freezing effect will result. If it is necessary to tilt the aerosol more than this, use the invertible version, EADI.

**Caution:** Do not use EAD/EADI for prolonged blasts as the surface of the can will form frost.

Revision 3: Jan 2019

#### **Copyright Electrolube 2013**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,  
Ashby de la Zouch,  
Leicestershire LE65 1JR  
T +44 (0)1530 419 600  
F +44 (0)1530 416 640  
BS EN ISO 9001:2008  
Certificate No. FM 32082