

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

RoHS₂
 2002/95/EC
 2011/65/UE

rightly blue

tasker® TSK1021 – 2x2,50 mm² - Extra Flex Speaker Cable



A	B	C	D
---	---	---	---

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Night Blue Soft PVC sheath.
Outer cable diam. Ø 9,00 (±0,10) mm.
- B:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester tape.
- C:** Core Insulation with a compact PE, colored one white and one red.
Diam. Ø 3,50 (±0,10) mm.
- D:** O.F.C. red copper formation 45x7x0,10 mm.
Wires stranded in beams and stranded again to create cores.
Nom. Cross section 2x2,50 mm².

MARKING tasker® TSK1021 2x2,5 mm² O.F.C. Extra Flex Loudspeakers Cable
CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	6,41 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			