



MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet



tasker® TSK403 – 2x2,50 mm²



Fix Installation Speaker Cable - CPR Cca Class



CATEGORY Fix Installation Speaker Cable (See News brochure)
APPLICATIONS Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Outer cable Ø: 8,90 (±0,20) mm.
- B:** Core Insulation in silicon rubber grade G4, colored one Red and one Black. Twisted together and grouped with PET tape. Diam. Ø: 3,40 (±0,20) mm.
- C:** O.F.C. red copper formation 48x0,25 mm. Nom. Cross section 2x2,50 mm².

MARKING **tasker® TSK403 2x2,50 mm² - O.F.C. Loudspeaker Cable - 0987-CPR-538 – 2022 – Cca – s1a – d0 – a1 – Uo/U 100/100 V – Firestop® - Halogen Free - Made in Italy**
NOTE The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

Cable Properties

Conductor Resistance	7,98 Ω/Km
Max Rated Voltage	100 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 29.05.20
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			