

Field Plug cat. 6_A FTP/STP

Rapid 6a



Field Plug cat. 6_A FTP/STP



IP20 resistance



Two types of wire manager



10Gbps bandwidth

Features

- Industry compatible design
- 360° shielding for better EMI/EMC
- Integrated strain relief
- Field and easy install
- Compatible with EN 50173 / ISO IEC 118

Norms

- Qualified Screened Class EA/Cat.6A
- Permanent Link & Channel ANSI/TIA-568-C.2
- IEC 60603-7-51
- ISO/IEC 11801 2.2 Edition
- CENELEC EN 50173-1:201

Field Plug FibrainDATA Cat.6_A FTP/STP

XR100.350

FOR 22-23 AND 24-26 AWG

ELECTRICAL AND MECHANICAL PARAMETERS

Maximum current value [A]	1.5
Insulation strength [MΩ] min	500
Contacts resistance [MΩ] max	20
DC Resistance [Ω] max	0.1
Compliance with the norm	IEC 11801 2nd Ed. Am. 1
Compliance with the norm	ANSI/TIA/EIA 568-C-2.1
Jacket	Shielded RJ45 cat. 6A
Housing	UL94V-0
Sequence identification	T568A and T568B



Field plug cat. 6_A FTP/STP

Manufacturing technology

